INDIRECT FIRED HEATERS



FVO-400



FVNP-400

MODEL	FVO-400	FVNP-400
Heat Capacity	up to 390,000 btuh	up to 390,000 btuh
Fuel Tank Capacity/Run Time	42 US Gallons / 14 hrs	External
Heater Dimensions/Weight	70” x 29” x 52” / 450 lbs	70” x 29” x 47” / 365 lbs
Heater Exchanger	16 Gauge 304 Stainless Steel	16 Gauge 304 Stainless Steel
Air Circulation	2,500 CFM - Ductable up to 50ft	2,500 CFM - Ductable up to 50ft
Air Outlet/Inlet	Outlet - 2 x 12” Dia. or 1 x 16” Dia.	Outlet - 2 x 12” Dia. or 1 x 16” Dia.
Wheels	16” Dia. Flat Free Wheels	16” Dia. Flat Free Wheels
Power Requirements	115V / 15Amp (10.5 Amp Draw)	115V / 15Amp (10.5 Amp Draw)

FEATURES:

Proven Riello burner technology including nozzle pre-heater for cold weather start up and upgraded low temperature fuel pump.
High density flat free wheels, and smart power indicator control Stainless Steel welded heat exchanger
Optional: Tiger-loop fuel filter system that eliminates fuel system air locks & 118 US Gallon Fuel Tank.