

Loader Specifications

	463	553	753	763	773	773 Turbo	863	873	963	864
--	-----	-----	-----	-----	-----	-----------	-----	-----	-----	-----

PERFORMANCE										
Rated Operating Capacity (SAE)	700 lbs. (318 kg)	950 lbs. (431 kg)	1300 lbs. (590 kg)	1500 lbs. (680 kg)	1750 lbs. (794 kg)	1850 lbs. (839 kg)	1900 lbs. (861 kg)	2400 lbs. (1089 kg)	3000 lbs. (1361 kg)	2000 lbs. (907 kg)
Optional with Counterweight Kit			1400 lbs. (635 kg)	1600 lbs. (706 kg)	1850 lbs. (839 kg)	1950 lbs. (884 kg)	2000 lbs. (907 kg)	2500 lbs. (1134 kg)	3650 lbs. (1656 kg)	
Hydraulic Pump Capacity	10 GPM (37,9 L/min.)	8.5 GPM (32,2 L/min.)	14.3 GPM (54 L/min.)	15 GPM (56 L/min.)	16.7 GPM (63 L/min.)	16.7 GPM (63 L/min.)	20 GPM (75,7 L/min.)	20 GPM (75,7 L/min.)	26.2 GPM (99.2 L/min.)	20.6 GPM (78 L/min.)
High Flow Capacity	n/a	n/a	n/a	n/a	27 GPM (102 L/min.)	27 GPM (102 L/min.)	30 GPM (113,6 L/min.)	30 GPM (113,6 L/min.)	n/a	32 GPM (121,1 L/min.)
Travel Speed	6.3 mph (10,1 km/hr.)	6 mph (9,7 km/hr.)	6.6 mph (10,6 km/hr.)	7 mph (11,3 km/hr.)	7 mph (11,3 km/hr.)	7 mph (11,3 km/hr.)	7.2 mph (11,6 km/hr.)	7.9 mph (12,7 km/hr.)	5.2 mph (8,4 km/hr.)	6.7 mph (10,8 km/hr.)
Two-Speed	n/a	n/a	n/a	n/a	n/a	n/a	12.5 mph (20,1 km/hr.)	12.5 mph (20,1 km/hr.)	9.0 mph (14,5 km/hr.)	n/a
Operating Weight	2708 lbs. (1228 kg)	3664 lbs. (1662 kg)	4740 lbs. (2150 kg)	5368 lbs. (2435 kg)	5808 lbs. (2635 kg)	5808 lbs. (2635 kg)	7045 lbs. (3196 kg)	7285 lbs. (3304 kg)	9900 lbs. (4491 kg)	8080 lbs. (3665 kg)

DIMENSIONS										
Length With Bucket	100.6 in. (2555 mm)	107.3 in. (2725 mm)	120.5 in. (3059 mm)	130.1 in. (3304 mm)	130.3 in. (3309 mm)	130.3 in. (3309 mm)	135.4 in. (3439 mm)	140.7 in. (3574 mm)	153.6 in. (3902 mm)	135.4 in. (3439 mm)
Width With Bucket	35.5 in. (901 mm)	49.4 in. (1255 mm)	55 in. (1398 mm)	68 in. (1727 mm)	68 in. (1727 mm)	68 in. (1727 mm)	74.0 in. (1879 mm)	74.0 in. (1879 mm)	79.6 in. (2022 mm)	74 in. (1880 mm)
Height	71.4 in. (1816 mm)	72.5 in. (1842 mm)	77 in. (1956 mm)	77.3 in. (1963 mm)	76.3 in. (1938 mm)	76.3 in. (1938 mm)	82.3 in. (2090 mm)	79.0 in. (2007 mm)	89.7 in. (2279 mm)	82.3 in. (2090 mm)
Height to Bucket Pin	94.5 in. (2347 mm)	103.7 in. (2634 mm)	109.1 in. (2771 mm)	114.5 in. (2909 mm)	118.2 in. (3002 mm)	118.2 in. (3002 mm)	121.0 in. (3073 mm)	124.3 in. (3158 mm)	128.0 in. (3252 mm)	121 in. (3073 mm)
Ground Pressure										
Narrow Tracks										5.2 psi w/12.6"
Wide Tracks										3.8 psi w/17.7"

ENGINE										
Cylinders	3	3	4	4	4	4	4	4	4	4
Fuel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel
Cooling	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Liquid	Oil	Oil	Oil
SAE Net HP	15.7 (11,7 kW)	22.5 (16,8 kW)	43.5 (32 kW)	46 (34 kW)	46 (34 kW)	56 (42 kW)	73 (54 kW)	73 (54 kW)	105 (78 kW)	73 (54 kW)
Displacement	44.0 in. ³ (0,72 L)	61.1 in. ³ (1,0 L)	134 in. ³ (2,2 L)	134 in. ³ (2,2 L)	134 in. ³ (2,2 L)	122 in. ³ (2 L)	178 in. ³ (2,92 L)	178 in. ³ (2,92 L)	243 in. ³ (3,99 L)	178 in. ³ (2,92 L)

FEATURES										
Auxiliary Hydraulics	std.	opt.	std.	std.	std.	std.	std.	std.	std.	std.
Bob-Tach Attachment System	std.	std.	std.	std.	std.	std.	std.	std.	std.	std.
Front and Rear Work Lights	opt.	opt.	std.	std.	std.	std.	std.	std.	std.	std.
Lift-Arm Support	std.	std.	std.	std.	std.	std.	std.	std.	std.	std.
Parking Brake	std.	std.	std.	std.	std.	std.	std.	std.	std.	std.
Top and Rear Windows	opt.	opt.	opt.	opt.	opt.	opt.	std.	std.	std.	std.
Seat Bar, Seat Belt	std.	std.	std.	std.	std.	std.	std.	std.	std.	std.
Suspension Seat	opt.	opt.	opt.	opt.	opt.	opt.	opt.	opt.	std.	std.
Spark Arrestor	std.	std.	std.	std.	std.	std.	std.	std.	std.	std.
BICS™ System	std.	std.	std.	std.	std.	std.	std.	std.	std.	std.
Hydraulic Bucket Positioning	opt.	opt.	opt.	opt.	opt.	opt.	opt.	opt.	std.	opt.
Bobcat Heavy-Duty Tires	opt.	opt.	opt.	std.	std.	std.	std.	std.	n/a	n/a
Sound Option	opt.	opt.	opt.	opt.	opt.	opt.	opt.	opt.	n/a	opt.
Cab Enclosure	opt.	opt.	opt.	opt.	opt.	opt.	opt.	opt.	opt.	opt.
Cab Heater	n/a	opt.	opt.	opt.	opt.	opt.	opt.	opt.	opt.	opt.
Cab Air Conditioning	n/a	n/a	n/a	n/a	n/a	opt.	opt.	opt.	opt.	opt.
Shutdown System	n/a	n/a	std.	std.	std.	std.	std.	std.	std.	std.