

TECHNICAL DATA

TAMPER

BT 30



Easy and ergonomic transport
Lightweight at around 66lb

Compact dimensions
Narrow tamper foot for tight spaces

Used in cable construction
Specially designed for cable and pipeline construction


Shipping dimensions in cub.yd
BT 30 0,229

Standard Equipment

- ☒ Engine Protection System
-Protective engine covering
- ☒ Vibration insulated steering handle
- ☒ Single point lifting device
- ☒ Recoil starter
- ☒ Infinitely variable frequency
- ☒ 3-2-1 Warranty

Optional Equipment

- ☐ Service Kit



Dimensions in inch

	B	H	L	L1	W
BT 30	12.4	37.4	23.0	10.7	5.5

Technical Data

BOMAG
BT 30

Weights

Operating weight	lb	71
Basic weight	lb	68

Dimensions

Working width (tamper plate)	in	5.5
------------------------------------	----	-----

Drive

Engine manufacturer		Honda
Engine type		GX 50
Emission stage		EU Stage V / EPA III
Cooling		air
Number of cylinders		1
Performance SAE J 1349	hp	2.0
Fuel		Gasoline
Drive system		mech.
Fuel consump. aver. during operation	gal/h	0.3

Exciter system

Frequency	vpm	600.0-792.0
Jumping height	in	1.8

Capacities

Fuel	gal	0.2
------------	-----	-----

Technical modifications reserved. Machines may be shown with options.



PRUS 540 67 010

080525 Sa

BOMAG Americas, Inc.
125 Blue Granite Parkway
Ridgeway, SC 29130
USA
Tel. +1 803 3370700
Fax +1 803 3370800
www.bomag.com/us

