

SPECIFICATIONS, FXT60

	U.S.	METRIC
DIMENSIONS		
Length	214.3 in	5443.2 mm
Width	96 in	2438.4 mm
Height	93 in	2362.2 mm
Weight, empty	6,700 lb	3039.1 kg
Truck GVWR, min	33,000 lb	14968.5 kg
POWER		
Engine	Deutz® TD2.9L4	
Fuel	Diesel	
Cooling medium	Liquid	
Aspiration	Turbocharged	
Number of cylinders	4	
Displacement	178 in³	2.9 L
Bore	3.62 in	92 mm
Stroke	4.33 in	110 mm
Manufacturer's gross power rating (SAE J1995)	74 hp	55 kW
Rated speed	2,600 rpm	
Emissions compliance	EPA Tier 4	EU Stage IIIB
Fuel tank capacity	25 gal	94 L

	U.S.	METRIC
VACUUM SYSTEM		
Blower displacement	1,027 cfm	29.1 m³/min
Drive type	Belt	
Vacuum, max	16 in Hg	406.4 mm Hg
Vacuum tank capacity, max	800 gal	3028 L
Full opening door diameter	52 in	1321 mm
Tank outlet valve size	6 in	152 mm
Tank inlet valve size	4 in	102 mm
Tank dump angle, max	45°	
Filter type	Washable polyester	
Filter rating	100 ft²	9.3 m²
Hose	4 in	101.6 mm
WATER SYSTEM		
Water tank capacity, max	400 gal	1514.2 L
Water pump flow	5.5 gpm	21 l/min
Water pump pressure, max	3,000 psi	207 bar
Clutch type	Electric pump clutch w/auto declutch feature	
Antifreeze system	50/50 water/antifreeze mix	
Hose length	50 ft	15.3 m
HYDRAULIC SYSTEM		
Flow rate	7.5 gpm	28 l/min
Reservoir size	6 gal	23 L
Pressure	2,500 psi	172 bar
BATTERY		
SAE reserve capacity rating	195 min	
SAE cold crank @ 0°F (-18°C)	950 amps	
Electrical system	12V	
NOISE LEVEL		
Sound power	110 dBA	
Sound pressure	82 dBA	

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.