



SPECIFICATIONS, SK350 MINI SKID STEER

	U.S.	METRIC
DIMENSIONS		
Overall height	42.5 in	1.1 m
Overall length	58.2 in	1.5 m
Width, excluding tracks	32 in	813 mm
Weight	1,660 lb	753 kg
Hinge pin height, max	70.4 in	1.8 m
Wheelbase/track length	30 in	762 mm
Track width, max	35.1 in	892 mm
Ground clearance		
Center	4 in	101 mm
Side	2.5 in	64 mm
Tipping capacity	1,030 lb	467 kg
Rated operating capacity		
35% of tipping capacity	350 lb	158 kg
Angle of departure	18°	
POWER		
Engine	Kohler® CH20	
Fuel	Gasoline	
Cooling medium	Air	
Number of cylinders	2	
Displacement	38 in³	624 cm³
Bore	3.03 in	77 mm
Stroke	2.64 in	67 mm
Gross power, installed net power per SAE J1349 @ 3,600 rpm	20 hp	14.9 kW
Rated speed	3,600 rpm	
OPERATION		
Ground drive speed		
Forward/reverse	3 mph	4.8 km/h
Ground pressure		
7-in (180-mm) tracks	4 psi	0.28 bar

	U.S.	METRIC
HYDRAULIC SYSTEM		
Auxiliary: gear pump	12 gpm	45.4 l/min
Pressure	2,300 psi	158 bar
Ground drive: dual hydrostat		
Flow rate	11 gpm	42 l/min
Pressure	2,330 psi	162 bar
FLUID CAPACITIES		
Fuel tank	7.5 gal	30.3 L
Engine oil	2 qt	1.9 L
Hydraulic reservoir	7 gal	26.5 L
BATTERY		
SAE reserve capacity rating	41 min	
SAE cold crank rating @ 0°F (-18°C)	340 amps	
Electrical system	12V	

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.