

Genie Z-25/8

Genie Z-20/8

Genie Z-20/8

Specifications

Z-20/8N

Height, working maximum	26 ft	7.9 m
Height, platform maximum	20 ft	6.1 m
Height, stowed maximum	6 ft 7 in	2.01 m
Horizontal reach maximum	8 ft 8 in	2.6 m
Width	32 in	81.3 cm
Length, stowed	12 ft 4 in	3.76 m
Maximum load capacity		
ANSI & CSA	400 lbs	181 kg
CE	440 lbs	200 kg
Wheelbase	5 ft 4 in	1.63 m
Turning radius (outside)	4 ft 9 in	1.4 m
Turning radius (inside)	10 in	25.4 cm
Ground clearance	1.625 in	4.1 cm
Jib boom rotation (degrees)		180°
Power source	8 6V 255AH batteries	

Drive speeds (maximum)

Boom stowed	2.6 mph 40 ft/10.5 sec	4.2 km/h 12.2 m/10.5 sec
Boom raised or extended	0.6 mph 40 ft/40 sec	1.0 km/h 12.2 m/40 sec
Gradeability (boom stowed)		18%
Controls	24V DC proportional	
Platform dimensions, (length x width)	31 x 40 in 78.7 x 101.6 cm	
AC outlet in platform	standard	
Hydraulic pressure (maximum) (boom functions)	3500 psi 241 bar	
Tires size	18x14x6	
Hydraulic tank capacity	8 gal	30.3 liters
Weight	10,750 lbs	4876 kg
Airborne noise emissions	67 dB	
Maximum sound level at normal operating workstations (A-weighted)		

Z-20/8

Height, working maximum	26 ft	7.9 m
Height, platform maximum	20 ft	6.1 m
Height, stowed maximum	6 ft 7 in	2.01 m
Horizontal reach maximum	7 ft 11 in	2.4 m
Width	46 in	117 cm
Length, stowed	11 ft 9 in	3.58 m
Maximum load capacity	500 lbs	227 kg
Wheelbase	5 ft 4 in	1.63 m
Turning radius (outside)	6 ft 4 in	1.9 m
Turning radius (inside)	11 in	28 cm
Ground clearance	2 in	5 cm
Jib boom rotation (degrees)		180°
Power source	8 6V 255AH batteries	

Drive speeds (maximum)

Boom stowed	2.7 mph 40 ft/10.1 sec	4.3 km/h 12.2 m/10.1 sec
Boom raised or extended	0.6 mph 40 ft/40 sec	1.0 km/h 12.2 m/40 sec
Gradeability (boom stowed)		20%
Controls	24V DC proportional	
Platform dimensions, (length x width)	46 x 30 in 117 x 76 cm	
AC outlet in platform	standard	
Hydraulic pressure (maximum) (boom functions)	3500 psi 241 bar	
Tires size	18x14x6	
Hydraulic tank capacity	8 gal	30.3 liters
Weight	7,000 lbs	3,175 kg
Airborne noise emissions	67 dB	
Maximum sound level at normal operating workstations (A-weighted)		

Continuous improvement of our products is a Genie policy.
Product specifications are subject to change without notice or obligation.

Genie Z-25/8

Genie Z-20/8

Genie Z-20/8

GENIE Z-25/8 SPECIFICATIONS

Z-25/8

Height, working maximum	31 ft	9.5 m
Height, platform maximum	25 ft	7.6 m
Height, stowed maximum	6 ft 7 in	2.01 m
Horizontal reach maximum	7 ft 11 in	2.4 m
Width	46 in	117 cm
Length, stowed	16 ft	4.9 m
Maximum load capacity	500 lbs	227 kg
Wheelbase	5 ft 4 in	1.63 m
Turning radius (outside)	6 ft 4 in	1.9 m
Turning radius (inside)	11 in	28 cm
Ground clearance	2 in	5 cm
Jib boom rotation (degrees)		180°
Power source	8 6V 255AH batteries	
Tail swing	18 in	45.7 cm
Nose swing	4 ft 10 in	1.5 m

Drive speeds (maximum)

Boom stowed	2.7 mph 40 ft/10.1 sec	4.3 km/h 12.2 m/10.1 sec
Boom raised or extended	0.6 mph 40 ft/40 sec	1.0 km/h 12.2 m/40 sec
Gradeability (boom stowed)		20%
Controls	24V DC proportional	
Platform dimensions, (length x width)	46 x 30 in 117 x 76 cm	
AC outlet in platform	standard	
Hydraulic pressure (maximum) (boom functions)	3500 psi 241 bar	
Tires size	18x14x6	
Hydraulic tank capacity	8 gal	30.3 liters
Weight	7,000 lbs	3,175 kg
Airborne noise emissions	67 dB	
Maximum sound level at normal operating workstations (A-weighted)		

Continuous improvement of our products is a Genie policy.
Product specifications are subject to change without notice or obligation.