

Model 10MSP

MOBILE STOCK PICKER

Features

- Heavy Duty Planetary Gear Drive Motors with 5 Times the Life of Previous Models
- Heavy Duty Pistol-Grip Joystick
- 4 Brush Direct Electric Drive
- Point & Go® One-Hand Drive and Steer System
- Proportional Drive and Elevate Controls
- Two Sealed 100 amp-hr Maintenance-Free Glass Mat (AGM) Batteries
- Automatic Five-Hour Battery Charger
- Battery Discharge Indicators—Platform and Base
- Heavy-Duty Anodized Aluminum Mast Sections
- Maintenance-Free Mast Guide System
- Strobe Lights Front and Rear
- Programmable Motion Alarm
- Slope Cut-Out Control Interlock
- Stand-On Foot Switch Operation Enable Control
- Platform Gate Operation Interlock
- Adjustable Height Material Tray
- Non-Marking Tire Material
- Built-in Fork Truck Pockets
- Lanyard Attachment Anchor
- Hourmeter
- Horn
- Shipping Skid
- Transportation Tie Downs
- Side and Front Bumpers
- ANSI, OSHA & CSA Compliant

Specifications

Dimensions:

Platform Height	10 ft (3.05 m)
Working Height	16 ft (4.88 m)
Drive Height	Max. Platform Height
Stowed Height	56 in. (142 cm)
Platform Entry Height	13 in. (33 cm)

Platform Capacity:

Stock Picking Platform	350 lb (159 kg)
Carry Deck Capacity	250 lb (113 kg)
Material Tray Capacity	250 lb (113 kg)

Platform Size (W x L):

20 x 27 in. (51 x 69 cm)

Overall Vehicle Length:

Chassis Length	60 in. (152 cm)
----------------	-----------------

Overall Vehicle Width:

Chassis Width	33 in. (84 cm)
Chassis Width w/o bumper	29.5 in. (75 cm)

Gross Vehicle Weight:

1,100 lb (499 kg)

Drive Maximum Speed:

Platform Lowered	3.5 mph (5.6 kmph)
Platform Elevated	0.6 mph (1 kmph)
Turning Radius	Zero
Gradeability	30%
Underclearance	2 in. (5 cm)

Wheel Diameter & Width:

Rear Drive & Steer Wheels	12.62 x 4 in. (32 x 10 cm)
Front Caster Wheels	8 x 2.5 in. (20 x 6 cm)
Tire Material	Non-Marking

Batteries:

Two Sealed 100 amp-hr Glass Mat (AGM)	
Battery Charger	25 Amp Automatic

Drive System:

4 Brush Direct Electric (planetary gear)



Accessories & Options

Charger Cord Retractor

Programmable 4-Digit Security Lock

Bike Carrier

Rug Carrier

Fluorescent Light Tube Caddy

Guide Roller System

JLG Industries, Inc.
1 JLG Drive
McConnellsburg, PA 17233-9533
Telephone 717-485-5161
Toll-free in US 877-JLG-LIFT
Fax 717-485-6417
www.jlg.com

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds ASME B56.6-2002 as originally manufactured for intended applications.

Form No.: SS-10MSP-0106
Part No.: 3132119
Printed in USA