

Model SSV10

STORE SUPPORT VEHICLE

Specifications

Dimensions:

Platform Height	10 ft (3.05 m)
Working Height	16 ft (4.88 m)
Drive Height:	Max. Platform Height
Stowed Height	56 in. (142 cm)
Platform Entry Height	13 in. (33 cm)

Platform Capacity:

Stock Picking Platform	350 lb (159 kg)
Material Tray	250 lb (113 kg)
Total Combined Capacity	600 lb (272 kg)

Platform Size (W x L):

Stock Picking Platform	20 x 27 in. (51 x 69 cm)
------------------------	--------------------------

Overall Vehicle Length:

Chassis Length	60 in. (152 cm)
----------------	-----------------

Overall Vehicle Width:

Chassis Width	33 in. (84 cm)
Chassis Width without Bumper	29.5 in. (75 cm)

Gross Vehicle Weight:

Stock Picking Platform	1,000 lb (454 kg)
------------------------	-------------------

Drive Maximum Speed:

Platform Lowered	4 mph (6.4 kmph)
Platform Elevated	0.6 mph (1 kmph)
Turning Radius	0
Gradeability	15%
Underclearance	0.625 in. (1.58 cm)

Wheel Diameter & Width:

Rear Drive & Steer Wheels	12.62 x 4 in. (32 x 10 cm)
Front Caster Wheels	8 x 2.5 in. (20 x 6 cm)
Tire Material	Non-Marking

Batteries:

Two Sealed 100 amp-hr Glass Mat (AGM)
Battery Charger 20 Amp Automatic

Drive System:

2 Brush Direct Electric (non-planetary gear)

Features

- Point & Go® One-Hand Drive and Steer System
- Proportional Drive and Elevate Controls
- Two Sealed 100 amp-hr Maintenance-Free Glass Mat (AGM) Batteries
- Automatic Five-Hour Battery Charger
- Battery Discharge Indicators at Platform and Base
- Heavy-Duty Anodized Aluminum Mast Sections
- Maintenance-Free Mast Guide System
- Strobe Lights Front and Rear
- Programmable Motion Alarm
- Flashing Amber Beacon (Descent)
- Slope Cut-Out Control Interlock
- Stand-On Foot Switch Operation Enable Control
- Platform Gate Operation Interlock
- Adjustable Height Material Tray
- Non-Marking Tire Material
- Built-in Fork Truck Pockets
- Lanyard Attachment Anchor
- Hourmeter
- Horn
- Shipping Skid
- Transportation Tie Downs
- Side and Front Bumpers
- ANSI, OSHA & CSA Compliant



Accessories & Options

Charger Cord Retractor

Programmable 4-Digit Security Lock

Bike Carrier

Rug Carrier

Fluorescent Light Tube Caddy

Guide Roller System

JLG Industries, Inc.

1 JLG Drive
McConnellsburg, PA 17233-9533
Telephone 717-485-5161
Toll-free in US 877-JLG-LIFT
Fax 717-485-6417
www.jlg.com

The JLG "1 & 5" Warranty

JLG Industries, Inc. backs our SP Series with our exclusive "1 & 5" Warranty. We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. These machines meet or exceed applicable OSHA Regulations in 29 CFR 1910.67, 29 CFR 1926.453, ANSI A92.3-1990 and CSA standard CAN3-B354.1-M82 as originally manufactured for intended applications. We reserve the right to make price, specification, and/or equipment changes without prior notification.

Form No.: SS-SSV10-0106
Part No.: 3132123
Printed in USA