

15VPSP

DRIVEABLE STOCK PICKER



Molded Step-In Platform with Material Tray



Stock Picking Platform



Extendible Platform



JLG®

Introducing the JLG 15VPSP Driveable Stock Picker

The 15VPSP Stock Picker lift creates a whole new dimension in stock picking productivity. Driveable at full platform height, the 15VPSP has the power and control features you need for improved access to confined or elevated work areas. Featuring the exclusive POINT & GO® joystick control system, a small footprint and zero turning radius, the 15VPSP provides unmatched drive and steer maneuverability even at full height.



POINT & GO®



Standard Features:

- Three platform choices
- POINT & GO® drive and steer
- Extruded aluminum mast with maintenance free guide system
- Automatic battery charger
- Battery condition indicator at the platform control
- Parking brake release for manual positioning
- Built-in fork pockets
- Automatically activated pothole protection
- Lanyard attachment point
- Safety control interlocks
- 1-½ degree tilt sensor and control
- Motion alarm
- Amber warning beacon
- Horn activated from the platform
- Hourmeter

Optional: Obstruction Sensor and Control System (OSCS)

SPECIFICATIONS

Working Height	21 ft. (6.40 m)
Platform Height	15 ft. 4 in. (4.67 m)
Drive Height	15 ft. 4 in. (4.67 m)
Platform Entry Height	17 in. (43 cm)
Overall Stowed Height	82 in. (2.08 m)
Overall Width	32 in. (81 cm)
Gross Vehicle Weight	2,190 lb. (993 kg)
Platform Total Capacity:	
Stock Picker Platform	500 lb. (230 kg)
Molded Platform & Material Tray*	400 lb. (181 kg)
Extension Platform*	400 lb. (181 kg)
Platform Size (W x L):	
Stock Picker Platform	28 x 48 in. (0.71 x 1.22 m)
Molded Platform & Material Tray	26 x 26 in. ea. (0.66 x 0.66 m)
Extension Platform - Extended	26 x 49 in. (0.66 x 1.24 m)
Overall Machine Length:	
Stock Picker Platform	73.5 in. (1.87 m)
Molded Platform & Material Tray	78 in. (1.98 m)
Extension Platform - Retracted	55 in. (66 cm)

*Preliminary rating

The JLG "1 & 5" Warranty

JLG Industries, Inc. backs our products with our exclusive "1 & 5" Warranty. We provide coverage on all products for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification.

This machine meets or exceeds applicable ANSI A92.6-1999, CAN3-B354.2-M82 and OSHA regulations in 29 CFR 1910.67 and 29 CFR 1926.453 as originally manufactured for intended applications.

JLG Industries, Inc.

1 JLG Drive
McConnellsburg, PA 17233-9553
Telephone 717-485-5161
Toll-free in US 877-JLG-LIFT
Fax 717-485-6417
www.jlg.com

