

User Manual of Product 1:

Louisville Ladder Fiberglass Extension Ladder, 28 feet,
300-pound duty rating, Type IA, FE3228, Orange

EXTENSION



SERIES FE3200

FIBERGLASS EXTENSION LADDER

300 LBS

LOAD CAPACITY

(Includes weight of user plus materials)



FE3220



LOUISVILLE
LADDER

BECAUSE WORK AIN'T PLAY.

MAX LOCK™



TOUGHEST
STRONGEST
LIGHTEST
RUNGLOCK **EVER**



COMPATIBLE
WITH MOST
ACCESSORY

OPTIONS

ANSI
Meets or exceeds requirements
of American National Standards Institute
ANSI A14.5



EXTENSION



SERIES FE3200



1 D-Rung

Direct rung to rail connection for a stronger connection.



2 Outside Slide Guides

Heavy duty metal slide guides



3 Swivel Shoe

Steel safety shoe with full metal boot.

Additional Accessories



Combination Pole Grip & Cable Hook

A rigid steel - plated V - shaped pole grip covered with rubber tread, combined with cable hook assembly FE3200-E03



Combination Spur and Shoe

Rotate spur down for extra security on penetrable surfaces. FE3200-E63



Aluminum Leveler

Automatic leveler keeps ladder level on uneven terrain

FE3200-E34

For More accessories and information visit LouisvilleLadder.com or see the back of your Louisville Ladder Catalog



MODELS	RAIL DEPTH
16' - 28'	3 1/4"
32'	3 5/16"
36' - 40'	3 11/32"

MODELS	STACK HEIGHT	INSIDE WIDTH		OUTSIDE WIDTH	
		BASE	FLY	BASE	FLY
16' - 28'	6 1/4"	14 11/16"	13 11/16"	17 1/16"	16 1/16"
32' - 40'	6 1/2"	15 5/16"	14 5/16"	17 11/16"	16 11/16"

MODEL	TOTAL LENGTH	LENGTH EACH SECTION	MAX. EXTENDED LENGTH	MAX. REACH	MAX. STANDING HEIGHT	APPROX. WEIGHT (LB)	APPROX. VOLUME (FT ³)
FE3216	16'	8'	13'	15' 11"	9' 4"	31	7.8
FE3220	20'	10'	17'	19' 10"	13' 3"	42	9.6
FE3224	24'	12'	21'	23' 8"	17' 1"	51	11.5
FE3228	28'	14'	25'	27' 7"	21'	60	13.4
FE3232	32'	16'	29'	31' 5"	24' 10"	67	16.2
FE3236	36'	18'	32'	34' 4"	27' 9"	84	15.8
FE3240	40'	20'	35'	37' 3"	30' 8"	92	17.5

*MAX. REACH = 5-FT 7-IN PERSON WITH 12-IN VERTICAL REACH



LOUISVILLELADDER.COM

1.800.666.2811