


MORBARK® 1100 TUB GRINDER

BENEFITS

- Full hydraulic tilt tub provides easy access to grates and anvil for routine maintenance
- Backed by a world class parts & service support team.
- Long lasting, durable machine that holds its value.
- Proven drive line protection system that protects against catastrophic damage from contaminants.



HAMMERMILL

Laser-cut, factory balanced hammermills with forged hammers offer unsurpassed durability and smooth operation.



HYDRAULIC AUGERS

Quickly remove product from beneath the mill. During material surges, pressure sensors on the auger system automatically slow tub rotation to prevent plugging.



TORQUE LIMITER

The full breakaway torque limiter system protects the engine and clutch against shock and overload without stalling the engine.



TUB TILT

Provides easy access to grates and anvil for routine maintenance.



SPECIFICATIONS

Note: Specifications may vary with equipment options

07082011

GENERAL

Length (operating).....	56'3"
Length (transport).....	37'2"
Height (transport)	12'9"
Width	11'2"
Gross weight NCL	48,630 lbs.
Axle weight NCL	34,830 lbs.
Tongue weight NCL	13,770lbs.
Gross weight WCL (optional).....	59,920 lbs.
Axle weight WCL (optional)	40,540 lbs.
Tongue weight WCL (optional).....	19,380 lbs.
Engine.....	CAT, or John Deere
Horsepower	500 HP to 700 HP
Fuel capacity (tank)	160 gallons
Hydraulic oil capacity NCL	120 gallons
Hydraulic oil capacity WCL.....	205 gallons

TUB

Tub has 9' diameter at inside base, and 62" deep, walls constructed of 3/8" reinforced steel plate, floor constructed of 1/2" thick wear-resistant steel, supported by 14 roller guides carried on 1-1/2" diameter shafts. Hydraulic full tilt tub for easy access to hammermill, with hydraulically powered variable RPM forward and reverse tub control; M.I.C.S. (Morbark Integrated Control System) tub controlled with automatic reversing tub, sensor system. Tub cover for debris containment.

Morbark Integrated Control System located in the instrument panel

HAMMERMILL AND SCREENS

24" x 52" Hammermill system constructed of heavy duty 16-1/2" diameter laser cut rotor, (13) 1-3/4" thick 2-piece laser-cut rotor plates to ensure precision and enforce steel strength. The plates are keyed on a 6-1/4" diameter rotor shaft with 3-15/16" bearings direct driven at engine RPM's and (8) 2" hammer retaining rods. Complete with (24) 2" balanced forged steel hard-surfaced hammers and (24) 2-15/16" replaceable hammerhead inserts with nuts and bolts

1" thick wear form steel heavy duty screens

DISCHARGE SYSTEM

Two 14" diameter augers discharge onto a 36" belt conveyor. Discharge height: 15'

Hydraulic fold for transport

Front hydraulic stabilizers and manual outriggers

OPTIONS

Magnetized end pulley

Dust suppression system

300 gallon fuel tank in lieu of 160 gallon fuel tank

Morbark reversing fan

Variety of screens

Air compressor

12' tub flare

Dual hydraulic tub drives

Available with cab and loader (as shown)



800-831-0042 989-866-2381

www.morbark.com