

New Holland Loader Specifications

7310



TT55 Tractor with 7310 Loader

TRACTOR COMPATIBILITY

TRACTOR PTO HORSEPOWER

Maximum lift height to pivot pin, in. (mm)
Dump clearance, in. (mm)
Digging depth, in. (mm)
Lift capacity, lbs. (kg)
Breakout force, lbs. (kg)
Reach @ maximum lift, in. (mm)
Bucket rollback, degrees
Bucket dump angle, degrees
Loader weight without bucket, lbs. (kg)

TT55, TT75 (2WD AND FWD ROPS ONLY)

42, 59
117 (2972)
88 (2235)
5 (127)
2,201 (998)
4,791 (2173)
34 (864)
23
45
800 (363)

Note: Loader specifications may vary based on tractor model, hydraulic system, tire size, etc.

PIN-ON LOADER BUCKETS

72-in. standard high volume material
84-in. heavy-duty material

QUICK-ATTACH LOADER BUCKETS

72-in. standard material
72-in. heavy-duty material
84-in. heavy-duty material
84-in. high volume, light material/snow

OTHER COMPATIBLE IMPLEMENTS

Bale spear

Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377

 **NEW HOLLAND IS A BRAND OF CNH.**
A GLOBAL LEADER IN AGRICULTURAL AND CONSTRUCTION EQUIPMENT AND FINANCIAL SERVICES.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.