

New Holland Loader Specifications

7308



TC30 Compact Tractor with 7308 Loader

TRACTOR COMPATIBILITY

- Maximum lift height to pivot pin, in. (mm)
- Clearance with bucket dumped, in. (mm)
- Reach @ maximum lift height, in. (mm)
- Maximum dump angle, degrees
- Maximum rollback angle, degrees
- Dig depth, in. (mm)
- Lift capacity to maximum height at bucket pivot pin, lbs. (kg)
- Breakout force at bucket pivot pin, lbs. (kg)
- Loader weight without bucket, lbs. (kg)
- Cycle times
 - Raise time, sec.
 - Lower time, sec.
 - Dump time, sec.
 - Rollback time, sec.

TC30
100.5 (2553)
84.0 (2134)
12.8 (324)
38
20
4.0 (102)
875 (397)
1602 (727)
516 (234)

Note: Loader specifications may vary based on tractor model, hydraulic system, tire size, etc.

PIN-ON LOADER BUCKETS	Struck	Heaped
60-in. standard material, cu. yd.	0.32	0.40
60-in. heavy duty material, cu. yd.	0.35	0.43
68-in. heavy duty material, cu. yd.	0.38	0.46

Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377

 **NEW HOLLAND IS A BRAND OF CNH.**
A GLOBAL LEADER IN AGRICULTURAL AND CONSTRUCTION EQUIPMENT AND FINANCIAL SERVICES.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.