



643E | Crawler


SENEBOGEN

40 t TELESCOPIC CRAWLER CRANE



 129 kW /  40 t /  30 m /  MULTICAB

Stage V



643 E

The all-rounder.

The 40 t telescopic crawler crane is a versatile all-rounder. With a load capacity of up to 40 t and a boom length of up to 43 m, it offers a wide range of applications. The telescopic crawler undercarriage ensures the necessary maneuverability even on rough terrain and small transport dimensions.

Its compact dimensions and powerful Full-Power Boom, which has also proven itself in other products of the series, mean that the SENNEBOGEN 643 E offers guaranteed flexibility on construction sites, especially in structural and civil engineering, as well as in infrastructure construction.



Ultimate ease of use

With a sound-proofed, flexibly mounted and optionally elevating comfort Multicab.

Maintenance & service

This is made easy with standard components and easy-to-access maintenance and service points.

More variety

Work optimally at all times with load hook, auxiliary jib, 6.5 m or 13 m fly jib. With the optional 13 m fly jib, boom lengths of up to 43 m are possible.

More flexibility

As the Full-Power Boom telescopes comfortably under load at any length and safely via the joystick. The telescopic crawler undercarriage can easily cope with even the most difficult terrain.

On site and ready to use fast

Easy to transport, including ballast. To the construction site, unload – off you go.

Photo shows the 643 E crawler in prefabricated part construction; Hungary

Advanced. The E Series

LONG SERVICE LIFE, HIGH VALUE RETENTION

- Reliable and powerful thanks to its robust construction and high-quality components.

SOPHISTICATED, STATE-OF-THE-ART TECHNOLOGY

- In the 5th generation – decades of experience in designing and constructing telescopic cranes




SIMPLE TO MAINTAIN AND SERVICE

- Technology that can be mastered and no over-engineering, easy access to all components

ENVIRONMENTALLY-FRIENDLY DRIVE TECHNOLOGY

- State-of-the-art engine, drive and emission systems in line with the latest technology standards (stage V)
- Large-scale pipes and valves for maximum efficiency

A MODULAR DESIGN. NUMEROUS APPLICATIONS.





43 m
BOOM LENGTH**

OUTSTANDING FLEXIBILITY. WITH THE FULL- POWER BOOM

- Impressive: the robust boom system can telescope easily and safely even with a load on the hook.
- Simple and convenient: can be operated using the joystick for any boom length, without needing to preselect length and load.
- Automatically optimal: always the best load capacity for each boom length.
- Steep things: Can work on inclines of up to 4°*.
- Comfortable work area: Maximum main boom length 30.0 m and folding 6.5 m or 13 m fly jib.

* with reduced load charts (optional)

** with 13 m fly jib (not shown)



Pick & Carry
30.2 t

at 4.0 m
radius

**COMPACT AND
STRONG.**
WITH MAXIMUM
FLEXIBILITY

- /// Pick & Carry: Lifting and moving loads
- /// High stability and optimum maneuverability even on narrow construction sites thanks to telescopic crawler undercarriage
- /// Optimal overview when lifting loads thanks to cab tiltable by 15° as standard
- /// Coverage of a large work area and flexibility thanks to a wide range of equipment options
- /// Radio remote control available



BETTER VIEW. BETTER SAFETY. FREE VIEW UPWARDS.

- Flexibly mounted, comfortable operator's cab with super sound-proofing
- Panoramic view with all-round glazing made from safety glass, with curved, hinged windshield, large skylight and rear window
- Optimal interior climate thanks to continuously adjustable cab heating and air conditioning
- Air-suspension comfort seat with seat heater, vibration damper, adjustable to any weight
- Ergonomic set up, resonant controls
- Radio with Bluetooth®
- Optional: Cab can be hydraulically elevated by 2.40 m and tilted by 20° (standard: 15°)

MULTICAB

THE PREMIUM CAB.





PANORAMIC VIEW
tiltable up to **15°**
as standard



TAKE FULL CONTROL WITH OUR JOYSTICKS

- Joysticks on resonant, seat-mounted consoles
- Comfortable grip thanks to ergonomic design
- Shortcuts for direct and sensitive control of all functions
- Operating comfort thanks to optimized design of buttons and switches



EASY TO TRANSPORT. READY FOR USE QUICKLY.

It is not just with procurement and operating costs that companies can make cost-effective decisions and savings. Astute contractors know that simple and economical transportation between construction sites is an important factor, too.



Economical


Thanks to the telescopic crawler undercarriage with a transport width of just 3.0 m, the 643 E fits easily on any standard low-loader.



approx. 42 t*

Complete

Thanks to its weight of approximately 42 t, the machine can be transported fully assembled.



Quick

Once it reaches the construction site, the machine is ready to use as soon as it has been unloaded.

MAINTENANCE AND SERVICE. MAKE IT EASY ON YOURSELF.



The SENCON control system supports you with diagnostics and makes troubleshooting easier. So your machine is back in action more quickly.

All maintenance and service points are arranged clearly and easily accessible. The clear labeling of components makes finding your way around easy.

KEEP IT SIMPLE. WITH TECHNOLOGY THAT CAN BE MASTERED.



Reliable and practical technology makes life easier. Where electronics add no value, we rely on hydraulics and electrical systems.



We make you happy, not reliant. With cost-effective components and fewer process steps, you can take care of the machine on your own.



At the central electrical distribution board, clearly arranged standard components simplify control and troubleshooting.

TECHNICAL DATA, EQUIPMENT

MACHINE TYPE

MODEL (TYPE) 643 Crawler

ENGINE

TYPE **Stage V:**
Cummins B4.5 FR95721
Rated power: 129 kW/2200 rpm
Operating point standard: 129 kW/2200 rpm
Operating point ECO: 129 kW/2050 rpm

Stage IIIa:
Cummins QSB4.5 FR96169
Rated power: 119 kW/2200 rpm
Operating point standard: 119 kW/2200 rpm
Operating point ECO: 119 kW/2050 rpm

both:
direct injection, turbocharged, charge air cooling, reduced emissions

COOLING water-cooled

DIESEL FILTER with water separator and heater

AIR FILTER Dry filter with integrated pre-separator, automatic dust discharge, main element and safety element, contamination indicator

FUEL 360 l

ADBLUE 38 l

ELECTRICAL SYSTEM 24 V

BATTERIES 2 x 155 AH

OPTIONS Low-temperature package with engine preheating and reinforced batteries

Electric fuel pump

UPPERCARRIAGE

DESIGN Torsion-resistant box design, precision crafted, steel bushings for boom mountings. Service-friendly design, engine installed in the longitudinal direction

ELECTRICAL SYSTEM Central electrical distributor, battery disconnect switch

LIGHTING LED headlights for optimal lighting of the work area

COOLING SYSTEM 3-circuit cooling system with high cooling output, electrically regulated fan drive for cooling water, charged air and oil

SAFETY Camera monitoring of the area to the rear and the right side

OPTIONS Additional LED headlights

2 warning beacons at the rear

Additional cameras

Sea climate resistant coating as corrosion protection

Customized paint finish

Low temperature package

Automatic central lubrication for boom attachment point, luffing cylinder and live ring track

Pinion tooth lubrication

Optional: Elevating cab; type E240



Optional: Additional LED lights on the basic boom



TECHNICAL DATA, EQUIPMENT

HYDRAULIC SYSTEM / HYDRAULICS



Pump unit attached directly to diesel engine. Load-sensing/ LUDV hydraulic system, electro-hydraulic work functions, load limit control, axial piston variable displacement pump. Multiple work functions can be controlled precisely simultaneously and independently from each other thanks to the independent, proportional allocation of the pump flows.

DELIVERY RATE up to 310 l / min

OPERATING PRESSURE up to 330 bar

FILTRATION High-performance filtration with long change interval

HYDRAULIC TANK 500 l

CONTROL SYSTEM Proportional, precision hydraulic control of the movements, 2 servo joysticks for work functions, additional functions via switches and foot pedals – arranged clearly and ergonomically

SAFETY Hydraulic circuits with safety valves
Pipe-fracture safety valves for luffing cylinder and telescopic cylinder

OPTIONS Bio-oil filling
SENNEBOGEN HydroClean micro-filter system (3 µm) with water separator
Hydraulic tank preheating

SLEWING DRIVE



GEARBOX Compact planetary gear with bent-axis hydraulic engine, integrated brake valves

SLEW BRAKE Spring-loaded multi-disk brake

SLEWING RING Large-scale, externally geared 1-row slewing ring

SLEWING SPEED 0-2 rpm, variable

CAB



CAB TYPE Multicab, 15° tiltable

CAB FEATURES Flexibly mounted, comfortable operator's cab with super sound-proofing. All-weather version, all-round glazing made from safety glass and a large skylight, opening windshield. Flexibly mounted comfort seat, weight adjustable and with vibration damper. Clear dashboard with swivel-mounted steering column. Continuously adjustable cab heating with air circulation control and particle filter, automatic air conditioning.

OPTIONS Hydraulically elevating cab type E240, can elevate up to 2.40 m and tilt by 20°

Auxiliary heating system with timer

Activated-carbon filter for cab

FOPS protective front grating

Protective roof grating

FOPS protective roof grating

Glazing of roof and windshield in bullet-proof glass design

Radio with USB and SD connections, MP3 and Bluetooth® functions



Option: additional LED headlight on the cab

TECHNICAL DATA, EQUIPMENT



Optional: radio remote control



Optional: Customized paint finish



Optional: 13 m fly jib extension

EQUIPMENT

BOOM	4-part with pulley head, hydraulically telescopic end-to-end from 9 to 30 m, adjustment speed -12° to 70° in approx. 35 sec; complete telescopic extension in approx. 100 sec.
CRANE SAFETY	Latest generation of load moment monitoring with event recorder, clear operations panel showing all important data via the SENCON display, lifting limit switch, cable exit protection, pressure relief valves and pipe fracture protection
CYLINDERS	Hydraulic cylinders with high-quality sealing and guide elements
OPTIONS	6.5 m fly jib, tiltable (0°, 40°), can be set up without auxiliary equipment, can be bolted to basic boom when not in use Fly jib extension to 13 m, tiltable (0°, 40°) Auxiliary jib 3.5 t load capacity, 1-strand, 2nd hook Customized paint finish Electro-hydraulic emergency unit Radio remote control Programmable working limit Additional load charts accepted for 2°/4° incline position SENtrack telemetry system



Optional: 2nd crane winch

TECHNICAL DATA, EQUIPMENT

UNDERCARRIAGE



DESIGN	Very strong, hydraulically telescopic crawler undercarriage, with integrated, protected drive transmission
DRIVE	Strong travel drive with 2-stage variable-displacement hydraulic engine and directly attached automatically functioning brake valve and compact planetary gear on each running gear side
PARKING BRAKE	Spring-loaded multi-disk brake
CRAWLER CARRIER	Maintenance-free tractor chassis with hydraulic chain tension, 700 mm triple grouser shoes
SPEED	0 - 2.7 km/h
OPTIONS	Floor plates in the following equipment: 800 mm triple grouser shoes 900 mm triple grouser shoes 700 mm flat track shoes

WINCH

The winches are driven via high-pressure-regulated adjustable hydraulic engines, so there is always optimal pulling force speed control. Hydraulic lowering brake valves for sensitive, wear-free braking. Strong oil bath planetary gears, low-maintenance. Holding brakes are spring-loaded, maintenance-free, low-wear disc brakes running in the oil bath, oil-cooled

35 kN tensile force (3rd position), cable speed 0-95 m/min., cable diameter 14 mm, max. cable length 160 m

SAFETY BRAKE Spring-loaded multi-disk brake

OPTIONS 2nd crane winch: 35 kN tensile force (3rd position), cable speed 0- 95 m/min., cable diameter 14 mm, max. cable length 130 m


OPERATING WEIGHT



MASS approx. 42,000 kg
With 30 m telescopic boom, 13 m fly jib, 35 t hook, 2 hoisting winches, with hydraulic telescopic undercarriage, ballast 7 t, undercarriage ballast 4 t

NOTE Operating weight varies by model and equipment.


Subject to technical changes.



CRANE EQUIPMENT



**MAIN BOOM
HA 30 m**



HOOK

CAPACITY [t]	WEIGHT [kg]	NUMBER OF FALLS								
		9	8	7	6	5	4	3	2	1
32 t (4-roll)	300 kg	31,500 kg	28,000 kg	24,500 kg	21,000 kg	17,500 kg	14,000 kg	10,500 kg	7,000 kg	3,500 kg
25 t (3-roll)	220 kg			24,500 kg	21,000 kg	17,500 kg	14,000 kg	10,500 kg	7,000 kg	3,500 kg
4 t (0-roll)	40 kg									3,500 kg

LOAD RATINGS



MAIN BOOM
HA 30 m



BALLAST
7.0 t



DIN
ISO



360°



UNDERCARRIAGE
BALLAST 4.0 t



TRACK WIDTH
3.8 m / 3.0 m / 2.3 m

RADIUS [m]		BOOM LENGTH [m]																				
		9.0			12.5			16.0			19.5			23.0			26.5			30.0		
																						
Undercarriage track width [m]	3.8	3.0	2.3	3.8	3.0	2.3	3.8	3.0	2.3	3.8	3.0	2.3	3.8	3.0	2.3	3.8	3.0	2.3	3.8	3.0	2.3	
2.0	40.0*	40.0*	40.0*																			
3.0	35.0	35.0	33.0	20.0	20.0	20.0	15.0	15.0	15.0	14.0	14.0	14.0	11.0	11.0	11.0	8.9	8.9	8.9	5.0	5.0	5.0	
4.0	30.2	27.7	20.2	20.0	20.0	19.9	15.0	15.0	15.0	14.0	14.0	14.0	11.0	11.0	11.0	8.9	8.9	8.9	5.0	5.0	5.0	
5.0	25.5	18.9	14.2	20.0	18.7	14.0	15.0	15.0	13.9	13.3	13.3	13.3	11.0	11.0	11.0	8.6	8.6	8.6	5.0	5.0	5.0	
6.0	18.0	14.1	10.7	18.5	13.9	10.5	14.9	13.8	10.5	12.0	12.0	10.9	10.3	10.3	10.3	8.3	8.3	8.3	5.0	5.0	5.0	
7.0	11.8/6.2	13.4/6.2	10.2/6.2	14.3	10.9	8.3	13.2	10.8	8.2	10.9	10.9	8.6	9.5	9.5	8.9	7.8	7.8	7.8	5.0	5.0	5.0	
8.0				11.5	8.8	6.7	11.4	8.7	6.6	9.8	9.1	7.0	8.7	8.7	7.3	7.4	7.4	7.4	5.0	5.0	5.0	
9.0				9.5	7.3	5.5	9.4	7.2	5.4	9.0	7.6	5.8	7.9	7.8	6.1	6.9	6.9	6.2	5.0	5.0	5.0	
10.0				7.5/9.6	6.5/9.6	4.9/9.6	8.0	6.1	4.5	8.3	6.4	4.9	7.1	6.7	5.1	6.4	6.4	5.3	5.0	5.0	5.0	
11.0							6.8	5.1	3.7	7.2	5.5	4.1	6.5	5.7	4.4	5.9	5.9	4.5	5.0	5.0	4.7	
12.0							5.9	4.4	3.1	6.2	4.7	3.5	5.9	5.0	3.7	5.5	5.2	3.9	5.0	5.0	4.1	
13.0							5.0	3.7	2.6	5.4	4.1	3.0	5.5	4.3	3.2	5.1	4.5	3.4	4.7	4.7	3.5	
14.0										4.8	3.6	2.6	5.0	3.8	2.8	4.8	4.0	3.0	4.4	4.1	3.1	
15.0										4.2	3.1	2.2	4.5	3.3	2.4	4.5	3.5	2.6	4.1	3.7	2.7	
16.0										3.7	2.7	1.9	4.0	2.9	2.1	4.2	3.1	2.3	3.8	3.3	2.4	
17.0										3.5/16.6	2.5/16.6	1.7/16.6	3.6	2.6	1.8	3.7	2.8	2.0	3.6	2.9	2.1	
18.0													3.2	2.3	1.6	3.4	2.5	1.7	3.3	2.6	1.9	
19.0													2.9	2.0	1.3	3.0	2.2	1.5	3.1	2.3	1.6	
20.0													2.6	1.8	1.1	2.7	2.0	1.3	2.9	2.1	1.4	
21.0													2.5/20.1	1.8/20.1	1.1/20.1	2.5	1.8	1.1	2.6	1.9	1.3	
22.0																2.2	1.6	1.0	2.4	1.7	1.1	
23.0																1.9/23.6	1.3/23.6	0.7/23.6	2.2	1.5	0.9	
24.0																			2.0	1.3	0.8	
25.0																			1.8	1.2	0.7	
26.0																			1.6	1.1	0.6	
27.0																			1.5	1.0	0.5	
28.0																			1.5/27.1	0.9/27.1	0.5/27.1	
Number of falls		10	10	10	6	6	6	5	5	5	4	4	4	4	4	4	3	3	3	2	2	2
I		0 %			50 %			100 %			100 %			100 %			100 %			100 %		
II		0 %			0 %			0 %			25 %			50 %			100 %			100 %		
III		0 %			0 %			0 %			25 %			50 %			100 %			100 %		
The load ratings must be reduced if there's a 13 m fly jib folded to the side of the main boom.																						
Load capacity reduction [kg]		570			420			330			280			240			210			180		

* only possible with special equipment


Subject to technical changes. See page 25 for notes on load charts.

CRANE EQUIPMENT



AUXILIARY JIB
HA-S

CRANE EQUIPMENT



LOAD RATINGS



AUXILIARY JIB
HA-S




BALLAST
7.0 t




DIN
ISO



360°



UNDERCARRIAGE
BALLAST 4.0 t



TRACK WIDTH
3.8 m / 2.3 m


RADIUS [m]	BOOM LENGTH [m]													
	9.0		12.5		16.0		19.5		23.0		26.5		30.0	
	0.75		0.75		0.75		0.75		0.75		0.75		0.75	
Undercarriage track width [m]														
3.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5/3.5	3.5/3.5
4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
5.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
6.0	3.5/6.7	3.5/6.7	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
7.0			3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
8.0			3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
9.0			3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
10.0			3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
11.0			3.5/10.2	3.5/10.2	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
12.0					3.5	3.0	3.5	3.4	3.5	3.5	3.5	3.5	3.5	3.5
13.0					3.5	2.5	3.5	2.9	3.5	3.5	3.5	3.5	3.5	3.5
14.0					3.5/13.7	2.1/13.7	3.5	2.5	3.5	3.1	3.5	3.3	3.5	3.4
15.0							3.5	2.1	3.5	2.7	3.5	2.9	3.5	3.0
16.0							3.5	1.8	3.5	2.3	3.5	2.5	3.5	2.6
17.0							3.1	1.5	3.5	2.0	3.5	2.2	3.5	2.3
18.0							3.0/17.2	1.4/17.2	3.1	1.7	3.5	1.9	3.2	2.0
19.0									2.8	1.5	3.3	1.6	3.0	1.8
20.0									2.5	1.2	2.9	1.4	2.8	1.5
21.0									2.2/20.7	1.0	2.6	1.2	2.5	1.3
22.0										0.8/20.7	2.4	1.0	2.3	1.2
23.0											2.1	0.9	2.1	1.0
24.0											1.8	0.7	1.9	0.8
25.0											1.7/24.2	0.6/24.2	1.7	0.7
26.0													1.5	0.6
27.0													1.4	0.5
28.0													1.4/27.1	
Number of falls	1	1	1	1	1	1	1	1	1	1	1	1	1	1
I	0 %		50 %		100 %		100 %		100 %		100 %		100 %	
II	0 %		0 %		0 %		25 %		50 %		100 %		100 %	
III	0 %		0 %		0 %		25 %		50 %		100 %		100 %	
The load ratings must be reduced if there's a 13 m fly jib folded to the side of the main boom.														
Load capacity reduction [kg]	570		420		330		280		240		210		180	

Tab. no.: 643R-30.0/75/1977/20/1216 HA-S
Tab. No.: 643R-30.0/75/1227/20/1216 HA-S

CRANE EQUIPMENT



FLY JIB
SA 6.5 m / SA 13 m



LOAD RATINGS



FLY JIB
SA 6.5 m



BALLAST
7.0 t



DIN
ISO



360°



UNDERCARRIAGE
BALLAST 4 t



TRACK WIDTH
3.8 m

RADIUS [m]	BOOM LENGTH [m]							
	9.0		16.0		23.0		30.0	
	6.5		6.5		6.5		6.5	
	—	△	—	△	—	△	—	△
3.8 m	0°	40°	0°	40°	0°	40°	0°	40°
2.0								
3.0	6.0		6.0					
4.0	6.0		6.0					
5.0	5.5	3.5	6.0		6.0			
6.0	4.9	3.3	6.0	3.6	6.0			
7.0	4.4	3.1	5.9	3.4	6.0		3.5	
8.0	4.0	2.9	5.4	3.3	5.9	3.4	3.5	
9.0	3.7	2.8	5.0	3.2	5.6	3.3	3.5	
10.0	3.4	2.7	4.6	3.1	5.3	3.2	3.5	3.2
11.0	3.1		4.3	3.0	5.0	3.2	3.5	3.0
12.0	2.8		4.1	2.8	4.7	3.1	3.5	2.9
13.0			3.9	2.8	4.4	3.0	3.5	2.8
14.0			3.7	2.8	4.2	2.9	3.3	2.7
15.0			3.5		3.9	2.9	3.0	2.5
16.0			3.3		3.7	2.8	2.8	2.4
18.0			2.9		3.3	2.7	2.4	2.3
20.0					2.7	2.6	2.1	2.1
22.0					2.2		1.9	1.9
24.0					1.7		1.8	1.7
26.0					1.4		1.5	1.6
28.0							1.2	
30.0							0.9	
32.0							0.7	
Number of falls	1	1	1	1	1	1	1	1
I	0 %		100 %		100 %		100 %	
II	0 %		0 %		50 %		100 %	
III	0 %		0 %		50 %		100 %	

Tab no.: 643R-30.0/75/197/77.0/08.06 SA6.5

CRANE EQUIPMENT

LOAD RATINGS



FLY JIB
SA 13 m



BALLAST
7.0 t



DIN
ISO



360°



UNDERCARRIAGE
BALLAST 4 t





TRACK WIDTH
3.8 m

RADIUS [m]		BOOM LENGTH [m]							
		9.0		16.0		23.0		30.0	
		13.0		13.0		13.0		13.0	
	3.8 m								
		0°	40°	0°	40°	0°	40°	0°	40°
3.0		3.0							
4.0		3.0							
5.0		3.0		3.0					
6.0		3.0		3.0					
7.0		2.9		3.0		3.0			
8.0		2.6		3.0		3.0			
9.0		2.3		2.9		3.0		2.0	
10.0		2.1	1.6	2.7		2.9		2.0	
11.0		2.0	1.5	2.5		2.7		2.0	
12.0		1.8	1.4	2.4	1.5	2.6		2.0	
13.0		1.7	1.4	2.2	1.5	2.5		2.0	
14.0		1.6	1.3	2.1	1.5	2.4	1.5	2.0	
15.0		1.6	1.3	2.0	1.4	2.3	1.5	2.0	
16.0		1.5	1.3	1.9	1.4	2.2	1.4	2.0	1.5
18.0		1.1		1.7	1.3	2.0	1.4	2.0	1.4
20.0				1.6	1.3	1.8	1.3	1.9	1.4
22.0				1.4		1.7	1.3	1.7	1.3
24.0				1.3		1.6	1.3	1.6	1.3
26.0						1.4	1.3	1.4	1.2
28.0						1.3		1.3	1.2
30.0						1.3		1.2	1.1
32.0						1.1		1.1	1.1
34.0								0.9	
36.0								0.7	
38.0								0.6	
Number of falls		1	1	1	1	1	1	1	1
I		0 %		100 %		100 %		100 %	
II		0 %		0 %		50 %		100 %	
III		0 %		0 %		50 %		100 %	

Tab. no.: 643R-30.0/75/1977/0/08.06 SA13.0

LOAD CAPACITY SCHEDULES

		MAIN BOOM HA			AUXILIARY JIB HA-S		FLY JIB SA 6.5 m			FLY JIB SA 13 m		
												
UNDERCARRIAGE TRACK WIDTH		 3.8 m	 3.0 m	 2.3 m	 3.8 m	 2.3 m	 3.8 m	 3.0 m	 2.3 m	 3.8 m	 3.0 m	 2.3 m
Counterweight [t]	Undercarriage ballast [t]											
 7.0 t	 4.0 t	 360°	 360°	 360°	 360°	 360°	 360°	-	-	 360°	-	-

Notes:


1. The specified load ratings given apply when the machine is on a firm and level ($\pm 0.3^\circ$) surface.
2. The load ratings are given in tons and apply for 360°.
3. The load ratings take the DIN 15019.2 and ISO 4305 standards into account.
4. The weight of the load handling equipment (hooks, suspension gear) should be deducted from the load capacities.
5. Load capacities must be limited or reduced in adverse conditions such as soft or uneven ground, slopes, wind, side loads, swinging loads, jolts or sudden stopping of loads, personnel and operators not experienced in handling loads.
6. Permissible cable pull per strand in crane mode for a cable diameter of 14 mm is 3,500 kg.
7. The load capacities given are for reference only. Please refer to the tables in the operating instructions for the relevant applicable load ratings.
8. Load capacities for tilts of 2°/4° are also available on request.

OPTIONAL EQUIPMENT




 **FLY JIB 6.5 m**
max. 2-strand, possible offset angles 0°/40°

 **FLY JIB EXTENSION TO 13 m**
6.5 m with 6.5 m extension, single strand, offset angle 0°/40°



 **AUXILIARY JIB**
3.5 t load capacity, 1-strand, 2nd hook

TRANSPORT DIMENSIONS




BASE PLATES	MIN. TRANSPORT WIDTH
700 mm	3000 mm
800 mm	3300 mm
900 mm	3400 mm

643 WITH T41/380 UNDERCARRIAGE AND 700 mm TRIPLE GROUSER SHOES

i Operating weight:

approx. 42 t (with 13 m fly jib, 2 hoisting winches, 7.0 t counterweight and 4.0 t undercarriage ballast as well as 35 t hook)



i Transport weight:


approx. 38 t (13 m fly jib, 2 hoisting winches, without undercarriage ballast)
approx. 42 t (13 m fly jib, 2 hoisting winches, with undercarriage ballast)

Dimensions in [mm]

ATTACHMENTS


FLY JIB 6.5 m

i Weight: 600 kg




FLY JIB EXTENSION 6.5 m

i Weight: 250 kg




AUXILIARY JIB

i Weight: 50 kg



Dimensions in [mm]



Construction site service crane; Germany



Hall construction; Great Britain



Cableway construction; Italy



SENNEBOGEN ACADEMY

Increase your knowledge because success is based on knowledge. In the SENNEBOGEN ACADEMY we place great importance on ensuring it flows powerfully.

➡ www.sennebogen-academy.com



SERVICE AND MAINTENANCE

Comprehensive customer service. And supply of spare parts. Service is a TOP priority for us.

➡ www.sennebogen.com/customer-service



SENtrack

Manage your fleet efficiently with SENtrack: Use information that would otherwise stay hidden and increase your efficiency:

➡ www.sennebogen.com/sentrack



RENTAL & USED

Discover the unique range of rental machines available from SENNEBOGEN Rental & Used. Find your rental machine here:

➡ www.sennebogen-rental-used.com

JOIN OUR OPERATORS' CLUB

The spotlight is on you and your machine! We focus on exclusive information, sharing experiences with other SENNEBOGEN operators as well as fun and enthusiasm.

All the benefits here ➡ www.sennebogen.com/operators-club



MOVE BIG THINGS – WITH US!



over **69**
of experience

100 %
family company

over **1600**
experienced
specialists worldwide

4
production plants in
Germany

over **180**
sales and service partners
worldwide

11
different telescopic
cranes



Telehandler
4-5.5 t

Balancer
130-300 t

Material handler
17-420 t

Duty cycle crane
13.5-300 t

Crawler crane
50-300 t

Telescopic crane
16-130 t

Port crane
300 t

643E | Crawler

Order no. 299154
643R-E-072110

This catalog describes machine models, the scope of equipment of individual models, and configuration options (standard equipment and optional equipment) of the machines delivered by SENNEBOGEN Maschinenfabrik GmbH. Machine illustrations may contain optional and supplementary equipment. Actual equipment may vary depending on the country to which the machines are delivered, especially in regard to standard and optional equipment. All product designations used may be trademarks of SENNEBOGEN Maschinenfabrik GmbH or other supplying companies, and any use by third parties for their own purposes may violate the rights of the owners.

Please contact your local SENNEBOGEN sales partner for information concerning the equipment variants offered. Requested performance characteristics are only binding if they are expressly stipulated upon conclusion of the contract. Delivery options and technical features are subject to change. All information is supplied without liability. Equipment is subject to change, and rights of advancement are reserved. © SENNEBOGEN Maschinenfabrik GmbH, Straubing, Germany. Reproduction in whole or in part only with written consent of SENNEBOGEN Maschinenfabrik GmbH, Straubing, Germany.

SENNEBOGEN
Maschinenfabrik GmbH
Hebbelstraße 30
94315 Straubing, Germany

➔ www.sennebogen.com

MOVE BIG THINGS

SALES SENNEBOGEN
Sales Crane Line
Tel. +49 9421 540-146
cranes@sennebogen.de

SPARE PARTS CENTER
Spare parts orders
spareparts@sennebogen.de

AFTER SALES
Technical support
service@sennebogen.de

