



Home > Equipment > Pile Driver > PD10

PD10 Specs

General Weights and Dimensions - 10 ' (3 m) Hammer		
Operating height	14.1'	4.3 m
Operating length	120"	304.8 cm
Operating width	119.3"	303 cm
Operating weight	13715 lbs	6221 kg
Transport Height	117"	297.2 cm
Transport Length	120"	304.8 cm
Transport Width	94.3"	239.5 cm

General Weights and Dimensions - 15 ' (4.6 m) Hammer		
Operating height	19.6'	6 m
Operating length	120"	304.8 cm
Operating width	119.3"	303 cm
Operating weight	14720 lbs	6676.9 kg
Transport Height	117"	297.2 cm
Transport Length	120"	304.8 cm
Transport Width	94.3"	239.5 cm

Operator's Station		
Roll over protection station (ROPS) rating	16300 lbs	7393.6 kg
Seat	Rotating	
Controls	Dual joystick	

Engine		
Make and Model	Yanmar TNV88	
Gross Horsepower	47 hp	35 kw
Number of Cylinders	4	
Cooling Medium	Liquid	
Fuel Type	Diesel	
EPA Certification Family	Tier 4i (Stage IIIB)	

Fluid Capacities		
Fuel Tank	17 gal	64.4 L
Engine crankcase with filter	2 gal	7.4 L
Hydraulic Tank	36 gal	136.3 L
Engine cooling system	1.5 gal	5.7 L

Ground Drive		
Hydraulic pump type	Sauer Danfoss H1 hydrostatic	
Maximum ground drive speed (low)	1.6 mph	2.6 km/h
Maximum ground drive speed (high)	2.6 mph	4.2 km/h
Track drive	Steel track with urethane pads	

Hammer		
Maximum angle (direction of travel)	11 deg	
Maximum angle (perpendicular to travel)	20 deg	
Standard hammer height	10'	3 m
Mast extension	5'	1.5 m
Impact drive type	High-frequency hammer	

Maximum hammer impact	1150	
------------------------------	------	--

Features		
Autoplumb	Standard	
Laser receiver	Optional	
Maximum laser operating distance	1500'	457.2 m

Copyright © 2010-2015. Vermeer Corporation. All Rights Reserved.

www.vermeer.com