



Home > Equipment > Bale Processors > BP8000

BP8000 Specs

Dimensions and Weights - Approximate		
Height - Forks Up	121"	307.3 cm
Height - Top of Deflectors	105"	266.7 cm
Width	108"	274.3 cm
Working Width - Top Discharge Door Down	132"	335.3 cm
Length - Forks Up	179"	454.7 cm
Length - Forks Down	197"	500.4 cm
Weight	3740 lbs	1696.4 kg
Tongue Weight	2 lbs	.91 kg
Tires	11L-15 Intermittent Highway Rated	

Tractor Requirements		
Hydraulic requirements	2 auxiliary remotes (1 with optional kit)	
Hydraulic Pressure	2000 psi	137.9 bar
Flow Rate	10 gpm	37.85 L/min

Options		
Flotation Tires	16.5L x 16.1 cleated	
Flow Control Valve	To control speed of the roller on tractors that do	
Work Lights	For use when processing hay after dark	

Standard Features

Capacity	2 bales, up to 6'x6', max 2500lbs. each	
Flail Drum Diameter	26.75"	67.9 cm
Flail Drum Length	72"	182.9 cm
Number of Flails	26	
Flail Size	7/16" x 5-9/16" tempered spring steel	
Safety Equipment	SMV sign, tail lights	
Twine Cutter	Used to cut twine off of the flail drum	

Attachment		
Horsepower Requirements	85 hp	63.38 kw

ATTACHMENTS

Copyright © 2010-2011. Vermeer Corporation. All Rights Reserved.

www.vermeer.com