



[Home](#) > [Equipment](#) > [Bale Processors](#) > [BPX9000](#)

BPX9000 Specs

Dimensions and Weights		
Length	15'	4.6 m
Height	8.5'	2.6 m
Width - Transport	8.2'	2.5 m
Width - Operation	11.2'	3.4 m
Weight	5060 lbs	2295.2 kg
Drawbar Weight	1460 lbs	662.2 kg

Tractor Requirements		
Horsepower Required	85 hp	63.4 kw
PTO speed	1000 rpm	
Hydraulics type	3- Double Acting	
Hydraulic Pressure	2000 psi	137.9 bar
Hydraulic flow rate	8 gpm	30.3 L/min

Standard Details		
Bale size capacity	Two Bales, 6' x 5'	
Bale weight capacity	2500 lbs	1134 kg
Flail Drum Speed	rpm	
Flail Quantity	30	
Flail description	7/16" x 5 9/16" tempered spring	
Flail Drum Diameter	26.8"	67.9 cm
Flail Drum Length	78"	198.1 cm

Slug bar quantity	7	
Slug bar adjustment	Hand Lever with 5 settings	
Tire Size - Standard	14L x 16.1FL	
Torque Protection - Driveline	Shear bolt	
Bale rotation	3 Roller Chains with Bolt-On Cross Slat	
Discharge Direction	Right Hand	
Hitch Jack	5000 lb. (2267.96kg)	

Optional Features		
Flotation Tires	16.5L- 16.1SL 6 SOFTRAC II	
Square bale kit	Yes	
Two remote kit	Yes	

Copyright © 2010-2011. Vermeer Corporation. All Rights Reserved.

www.vermeer.com