



Home > Equipment > Mini Skid Steers > S650TX

S650TX Specs

General Dimensions and Weights		
Design	Stand-on / track-drive	
Length with Standard Bucket	91.5"	232.4 cm
Length without Standard Bucket	71.5"	181.6 cm
Width with Standard Bucket	42"	106.7 cm
Width Without Standard Bucket	36.5"	92.7 cm
Height	57.8"	146.8 cm
Height (to Hinge Pin)	80"	203.2 cm
Ground Clearance	5"	12.7 cm
Weight (Standard Bucket, Diesel Engine)	2690 lbs	1220.2 kg
Weight (No Bucket, Diesel Engine)	2560 lbs	1161.2 kg

Engine Option One		
Make and Model	Kubota D1105-ET03	
Fuel Type	Diesel	
Fuel Tank Capacity	14.5 gal	54.9 L
Gross Horsepower	24.8 hp	18.5 kw
Cooling System	Liquid	
Maximum Angle of Inclination	30 deg	

Track Performance		
Rated Operating Capacity (SAE)	660 lbs	299.4 kg
Tipping Capacity (With 175 lb (79.38 kg) operator)	1890 lbs	857.3 kg
Travel Speed	4.5 mph	7.2 km/h
Ground Pressure (Narrow Tracks)	4.5 psi	31 kPa
Ground Pressure (Wide Tracks)	3.6 psi	24.8 kPa

Operational		
Steering	Single, pilot-operated joystick	
Lift	Single, dual axis	
Curl	Single, dual axis	

Hydraulic System		
Hydraulic System Flow	13.5 gpm	51.1 L/min
Hydraulic System Pressure	2950 psi	203.4 bar
Tank capacity	11 gal	41.6 L

ATTACHMENTS

Copyright © 2010-2014. Vermeer Corporation. All Rights Reserved.

www.vermeer.com