



[Home](#) > [Equipment](#) > [Plows](#) > [PTX40](#)

PTX40 Specs

General Dimensions and Weights		
Weight (basic tractor, rubber tires)	2740 lbs	1242.8 kg
Weight (basic tractor, rubber tires, option two)	2780 lbs	1261 kg
Weight (basic tractor, rubber tires, option three)	3028 lbs	1373.5 kg
Length (basic tractor, rubber tires)	84.8"	215.4 cm
Length (basic tractor, rubber tires, option two)	84.8"	215.4 cm
Length (basic tractor, rubber tires, option three)	84.8"	215.4 cm
Width (basic tractor, rubber tires)	40.2"	102.1 cm
Width (basic tractor, rubber tires, option two)	48"	121.9 cm
Width (basic tractor, rubber tires, option three)	60"	152.4 cm
Height (basic tractor, rubber tires)	55"	139.7 cm
Height (basic tractor, rubber tires, option two)	56.5"	143.5 cm
Height (basic tractor, rubber tires, option three)	55"	139.7 cm
Ground Clearance (rubber tires)	6.4"	16.3 cm

Ground Clearance (rubber tires, option two)	7.9"	20.1 cm
Angle of approach (basic tractor, rubber tires)	32 deg	
Angle of approach (basic tractor, rubber tires, option two)	37 deg	

Engine Option One		
Make and Model	Kubota WG1605	
Manufacturer's gross hp rating	46.8 hp	34.9 kw
Maximum Torque	88.7 ft-lb	120.3 Nm
Number of Cylinders	4	
Cooling Medium	Liquid-cooled	
Fuel Type	Gasoline	
Emissions rating	EPA phase 3 and CARB LSI	

Capacities		
Fuel Tank	12 gal	45.4 L
Hydraulic Tank	9 gal	34.1 L
Hydraulic System	11 gal	41.6 L
Coolant	1.3 gal	4.9 L

Ground Drive - Rubber Tire		
Tire size	23 X 10.5-12 - singles or duals	

Ground Drive - Rubber Tires - Option 2		
Tire size	26 X 12 - 12	

Axle Options		
Front Axle Type	Planetary	

Rear Axle Type	Planetary	
Outside Turning Diameter (Rubber Tires Option Two, Front and Rear Steer)	19'	5.8 m
Outside turning diameter (rubber tires option three, front and rear steer)	20'	6.1 m

Electrical System		
System Voltage	12	

ATTACHMENTS

Copyright © 2010-2015. Vermeer Corporation. All Rights Reserved.

www.vermeer.com