



**WACKER
NEUSON**
all it takes!

SW32

Skid Steer Loader

Productivity Personified

The SW32 is the most powerful and largest Skid Steer Loader in the Wacker Neuson product line. Versatile and comfortable, the SW32, has the speed and control to maximize efficiency. Equipped standard with 2-speed and a color 5.7" multi-function display, allowing in-cab control customizations, the SW32 will enhance productivity on any jobsite.

Highlights

- Controls for Every Operator
- Filter Free After-treatment
- Expansive Maintenance Access

Technical Data

Hydraulic

flow rate	25,1 gal/mi
flow rate max.	37,2 gal/mi
Auxiliary relief pressure	3.987,5 psi

Mechanical - Output Details

Break Out Force Bucket	7.932,4 lbf
Break Out Force Lift Arm	9.371,4 lbf
Tractive Effort max.	9.711,7 lbf
travel speed stage 1	7,3 m/H
travel speed stage 2	12,2 m/H

Mechanical Details

Length without Bucket	117,5 "
Length with Bucket	145,4 "
Overall width without bucket	71,9 "
Height to top of ROPS	83,2 "
Bucket Hinge Pin Height	134,8 "
Angle of departure	23,0 °
Bucket height at height max.	107,8 "

Buck. dump angle at height max	44,0 °
Operating weight	8.628,9 lb
Ground clearance	8,9 "
Wheelbase	49,9 "

Engine

Cooling	water-cooling
Engine type	Diesel engine
Cylinder	4,0
Cylinder capacity	205,0 Inch3
Operating power	100,6 hp
Operating Engine speed	2.500,0 1/min
Battery capacity (nom. value)	950,0 Ah
Manufacturer	Kohler

Operating Fluids

Fuel Tank capacity	39,9 gal US
--------------------	-------------

Chassis

Tip Load	6.400,0 lb
Nennbetriebskapazität bei 50% Kipplast	3.198,9 lb

Dimensions

A1	Overall length with bucket	145.4 in
B1	Overall length without bucket	117.5 in
E1	Wheelbase	49.9 in
F1	Hinge pin height	134.8 in
G1	Dump height max.	107.8 in
L1	Ground clearance	9 in
M1	Angle of departure	23 °