

Road Construction & Maintenance Machinery



XP163 Pneumatic Roller



- **Product Category:** Road Machinery
- **Brand:** XCMG
- **Model:** XP163
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of XP163 Pneumatic Roller

XP163 tyre roller is a large-tonnage tyre roller produced according to market requirements, which will take pneumatic tyres as working device for compacting paved materials. The tyre roller is mainly applicable for compacting operation of asphalt pavement, foundation layer, secondary foundation layer, dam and filling engineering. It is an ideal set of compacting equipment for building high grade highway, airport, port, dam and industrial construction site.

Parameters of XP163 Pneumatic Roller

Item		Unit	XP163
Maximum operating mass		kg	16000
Ground pressure		kPa	150~ 300
Travel speed	Gear I	km/h	4
	Gear II	km/h	8.3
	Gear II	km/h	17.5
Theoretical gradeability		%	20
Minimum turning radius		mm	7330
Minimum ground clearance		mm	260
Compaction width		mm	2250
Overlapped volume of roller		mm	45
Tires	Specification		11.00-20
	Quantity		Front 4 rear 5
Engine	Type		SC4H115.4G2B
	Rated power	kw	86
	Fuel consumption	g/kw.h	≤205
Total length		mm	4800
Total width		mm	2356
Total height		mm	3330
Diesel tank volume		L	150
Water tank volume		L	650