

Road Construction & Maintenance Machinery



XP203 Pneumatic Roller



- **Product Category:** Road Machinery
- **Brand:** XCMG
- **Model:** XP203
- **Price:** \$100000.00-\$1000000.00 / EA
- **Delivery Time:** 1-90DAYS
- **Supply Capacity:** 1-500UNITS / Year
- **Product Origin:** China
- **After-sales Service:** Engineers available to service machinery overseas.

Product Feature of XP203 Pneumatic Roller

XP203 pneumatic tire roller is a large-tonnage pneumatic tire roller produced according to market requirements, which will take pneumatic tires as working device for compacting paved materials. The pneumatic tire roller is mainly applicable for compacting operation of asphalt pavement, foundation layer, secondary foundation layer, dam and filling engineering. It is an ideal set of compacting equipment for building high grade highway, airport, port, dam and industrial construction site.

Parameters of XP203 Pneumatic Roller

Description		Unit	Parameter value
Minimum work weight		kg	11750
Maximum working weight		kg	20000
Counterweight water		kg	650
Counterweight mass		kg	7600
Ground pressure		kPa	200-400
Driving speed	I	km/h	4
	II		8.3
	III		17.5
Theoretical climbing ability		%	20
Minimum turning radius		mm	7330
Minimum ground clearance		mm	260
Compaction width		mm	2250
Tire overlao		mm	45
Tire specifications			11.00-20-16PR
Tire arrangement			Front 4 Back 5
Engine model			SC4H115.4G2B
rated power		kw	86
Fuel consumption		g/kw.h	≤205 (1±5%)
Total length		mm	4800
Total width		mm	2356
Total height		mm	3330

